



SPECIFICATION/HOW TO ORDER/NOMENCLATURE



Fractional Hp Clutches & Brakes

SPECIFICATION

The Fractional HP product offerings include three shaft mounted clutches and three flange mounted brakes. In the shaft mounted line, the SL and BSL series are used to couple two parallel shafts, and the SO series is used to couple two in-line shafts. They are engineered for easy installation, and incorporate a zero backlash armature hub assembly. In the flange mounted line, the FB series is "power-on" and the FSB and FSBR series are "power-off".

HOW TO ORDER

Fractional HP Clutches and Brakes are ordered by specifying the type of unit, size, voltage and bore size. Part numbers are found on the selection pages for each type of unit. Refer to the part number when ordering.

NOMENCLATURE

SL 15 - 90 x 38"

TYPE

SL Shaft Mounted Clutch
 BSL Ball Bearing Mounted Clutch
 SO Shaft Mounted Clutch Coupling
 FB Flange Mounted Brake
 FSB Fail Safe (Power-off) Brake
 FSBR Fail Safe (Power-off) Brake
 Reverse Mount

SIZE (Approximate O.D. of Unit)

VOLTAGE

24 VOLT
 90 VOLT
 * Other Voltages Available by Special Order

BORE SIZE

FEATURES/BENEFITS PAGE PT2-25	SELECTION/DIMENSIONS PAGE PT2-31	MODIFICATION PAGE PT2-37	ENGINEERING/TECHNICAL PAGE PT2-39
----------------------------------	-------------------------------------	-----------------------------	--------------------------------------