



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
0.25	65	26.90	726	242	3	7.03	B_383GH71C4
	55	31.59	926	284	3	7.79	
	48	36.69	926	330	3	6.71	
	44	39.73	926	358	3	6.18	
	39	44.94	1150	405	3	5.46	
	35	49.38	1150	445	3	4.97	
	32	54.47	1150	490	3	4.52	
	29	60.33	1150	543	3	4.08	
	26	67.18	1150	605	3	3.66	
	23	77.09	1411	694	3	3.19	
	21	85.33	1411	768	3	2.88	
	18	97.05	1411	874	3	2.53	
	16	110.75	1411	997	3	2.22	
	14	124.78	1411	1123	3	1.97	
	13	139.43	1411	1255	3	1.76	
	11	159.04	1411	1432	3	1.55	
	10	179.13	1411	1613	3	1.37	
	64	27.55	1149	248	3	7.35	B_483GH71C4
	29	60.08	1591	541	3	7.36	
	26	66.60	1591	600	3	6.64	
	23	75.45	1878	679	3	5.87	
	21	83.25	1878	750	3	5.31	
	19	94.12	1878	847	3	4.70	
	16	107.47	1878	968	3	4.11	
	14	122.19	1878	1100	3	3.62	
	13	130.78	1878	1177	3	3.38	
	12	150.76	1878	1357	3	2.94	
	10	169.53	1878	1526	3	2.61	
	16	109.64	2503	987	3	7.29	B_683GH71C4
	14	126.09	2503	1135	3	6.39	
13	136.60	2503	1230	3	5.90		
12	150.98	2503	1359	3	5.34		
10	176.14	2503	1586	3	4.58		
9	196.07	2503	1765	3	4.11		
8	215.68	2503	1942	3	3.74		
7	243.72	2503	2194	3	3.31		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
0.25 (CONT')	10	176.50	4512	1589	3	6.81	B_883GH71C4
	9	193.24	4512	1740	3	6.31	
	8	215.25	4512	1938	3	5.76	
	7	246.13	4512	2216	3	5.13	
	6	272.95	4512	2458	3	4.68	
	6	302.68	4512	2725	3	4.27	
0.33	310	5.65	589	67	3	6.13	B_383GH71D4
	281	6.22	589	74	3	6.11	
	242	7.22	620	86	3	6.11	
	224	7.82	620	93	3	6.11	
	198	8.85	620	105	3	6.12	
	180	9.72	620	116	3	6.09	
	163	10.72	620	127	3	6.14	
	152	11.50	617	137	3	6.10	
	138	12.65	617	150	3	6.13	
	119	14.69	617	175	3	6.10	
	110	15.91	617	189	3	6.12	
	97	17.99	726	214	3	6.11	
	88	19.78	726	235	3	6.12	
	80	21.81	726	259	3	6.12	
	72	24.16	726	287	3	5.74	
	65	26.90	726	320	3	5.32	
	61	28.72	926	341	3	6.12	
	55	31.59	926	375	3	5.90	
	48	36.69	926	436	3	5.08	
	44	39.73	926	472	3	4.69	
	39	44.94	1150	534	3	4.14	
	35	49.38	1150	587	3	3.77	
	32	54.47	1150	647	3	3.42	
	29	60.33	1150	717	3	3.09	
	26	67.18	1150	798	3	2.77	
	23	77.09	1141	916	3	2.42	
21	85.33	1141	1014	3	2.18		
18	97.05	1141	1153	3	1.92		
16	110.75	1141	1316	3	1.68		
14	124.78	1141	1483	3	1.49		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
0.33 (CONT.)	13	139.43	1141	1657	3	1.34	B_383GH71D4
	11	159.04	1141	1890	3	1.17	
	10	179.13	1141	2129	3	1.04	
	188	9.32	1032	111	3	6.10	B_483GH71D4
	172	10.15	1032	121	3	6.10	
	113	15.42	1110	183	3	6.13	
	104	16.79	1110	200	3	6.10	
	93	18.78	1149	223	3	6.12	
	85	20.54	1149	244	3	6.12	
	78	22.54	1149	268	3	6.11	
	70	24.85	1149	295	3	6.01	
	64	27.55	1149	327	3	5.57	
	61	28.90	1266	343	3	6.13	
	52	33.60	1266	399	3	6.12	
	47	37.28	1266	443	3	6.12	
	43	40.60	1266	483	3	6.11	
	39	45.41	1591	540	3	6.11	
	35	49.65	1591	590	3	6.12	
	32	54.49	1591	648	3	6.11	
	29	60.08	1591	714	3	5.58	
	26	66.60	1591	792	3	5.03	
	23	75.45	1878	897	3	4.44	
	21	83.25	1878	989	3	4.03	
	19	94.12	1878	1119	3	3.56	
	16	107.47	1878	1277	3	3.12	
	14	122.19	1878	1452	3	2.74	
	13	130.78	1878	1554	3	2.56	
	12	150.76	1878	1792	3	2.22	
	10	169.53	1878	2015	3	1.98	
	206	8.50	2503	101	3	6.12	B_683GH71D4
184	9.52	2503	113	3	6.13		
168	10.40	2503	124	3	6.10		
92	18.93	2503	225	3	6.12		
82	21.22	2503	252	3	6.12		
76	23.16	2503	275	3	6.12		
69	25.42	2503	302	3	6.12		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
0.33 (CONT.)	63	27.99	2503	333	3	6.11	B_683GH71D4
	58	30.38	2503	361	3	6.12	
	34	51.96	2503	618	3	6.11	
	30	58.23	2503	692	3	6.12	
	28	63.57	2503	756	3	6.11	
	25	69.78	2503	829	3	6.12	
	23	76.84	2503	913	3	6.12	
	21	83.40	2503	991	3	6.12	
	19	90.89	2503	1080	3	6.12	
	18	99.55	2503	1183	3	5.95	
	16	109.64	2503	1303	3	5.52	
	14	126.09	2503	1499	3	4.84	
	13	136.60	2503	1623	3	4.47	
	12	150.98	2503	1794	3	4.05	
	10	176.14	2503	2093	3	3.47	
	9	196.07	2503	2330	3	3.11	
	8	215.68	2503	2563	3	2.83	
	7	243.72	2503	2897	3	2.51	
	69	25.53	4512	303	3	6.13	B_883GH71D4
	61	28.50	4512	339	3	6.11	
	57	30.87	4512	367	3	6.12	
	23	75.45	4512	897	3	6.12	
	21	84.21	4512	1001	3	6.12	
	19	91.22	4512	1084	3	6.12	
	17	103.38	4512	1229	3	6.12	
	16	111.37	4512	1324	3	6.12	
	15	120.42	4512	1431	3	6.12	
	13	130.77	4512	1554	3	6.12	
12	144.58	4512	1718	3	6.08		
11	156.63	4512	1862	3	5.69		
10	176.50	4512	2098	3	5.16		
9	193.24	4512	2297	3	4.78		
8	215.25	4512	2558	3	4.36		
7	246.13	4512	2925	3	3.88		
6	272.95	4512	3244	3	3.55		
6	302.68	4512	3597	3	3.23		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER	
0.5	310	5.65	589	102	3	4.03	B_383GH71E4	
	281	6.22	589	112	3	4.04		
	242	7.22	620	130	3	4.04		
	224	7.82	620	141	3	4.03		
	198	8.85	620	159	3	4.04		
	180	9.72	620	175	3	4.04		
	163	10.72	620	193	3	4.04		
	152	11.50	617	207	3	4.04		
	138	12.65	617	228	3	4.03		
	119	14.69	617	265	3	4.03		
	110	15.91	617	286	3	4.04		
	97	17.99	726	324	3	4.04		
	88	19.78	726	356	3	4.04		
	80	21.81	726	393	3	4.04		
	72	24.16	726	435	3	3.79		
	65	26.90	726	484	3	3.52		
	61	28.72	926	517	3	4.04		
	55	31.59	926	569	3	3.89		
	48	36.69	926	661	3	3.35		
	44	39.73	926	715	3	3.09		
	39	44.94	1150	809	3	2.74		
	35	49.38	1150	889	3	2.49		
	32	54.47	1150	981	3	2.26		
	29	60.33	1150	1086	3	2.04		
	26	67.18	1150	1210	3	1.83		
	23	77.09	1411	1388	3	1.59		
	21	85.33	1411	1537	3	1.44		
	18	97.05	1411	1748	3	1.27		
	16	110.75	1411	1994	3	1.11		
	242	7.22	1032	130	3	4.04		B_483GH71E4
	208	8.40	1032	151	3	4.04		
	188	9.32	1032	168	3	4.03		
172	10.15	1032	183	3	4.03			
146	11.95	1110	215	3	4.04			
126	13.90	1110	250	3	4.04			
113	15.42	1110	278	3	4.03			

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
0.5 (CONT.)	104	16.79	1110	302	3	4.04	B_483GH71E4
	93	18.78	1149	338	3	4.04	
	85	20.54	1149	370	3	4.04	
	78	22.54	1149	406	3	4.04	
	70	24.85	1149	447	3	3.97	
	64	27.55	1149	496	3	3.68	
	61	28.90	1266	520	3	4.04	
	52	33.60	1266	605	3	4.04	
	47	37.28	1266	671	3	4.04	
	43	40.60	1266	731	3	4.04	
	39	45.41	1591	818	3	4.04	
	35	49.65	1591	894	3	4.04	
	32	54.49	1591	981	3	4.04	
	29	60.08	1591	1082	3	3.68	
	26	66.60	1591	1199	3	3.32	
	23	75.45	1878	1359	3	2.93	
	21	83.25	1878	1499	3	2.66	
	19	94.12	1878	1695	3	2.35	
	16	107.47	1878	1935	3	2.06	
	14	122.19	1878	2200	3	1.81	
	13	130.78	1878	2355	3	1.69	
	12	150.76	1878	2715	3	1.47	
	10	169.53	1878	3053	3	1.30	
	206	8.50	2503	153	3	4.04	B_683GH71E4
	184	9.52	2503	171	3	4.05	
	168	10.40	2503	187	3	4.04	
	92	18.93	2503	341	3	4.04	
	82	21.22	2503	382	3	4.04	
	76	23.16	2503	417	3	4.04	
	69	25.42	2503	458	3	4.04	
63	27.99	2503	504	3	4.04		
58	30.38	2503	547	3	4.04		
34	51.96	2503	936	3	4.04		
30	58.23	2503	1049	3	4.04		
28	63.57	2503	1145	3	4.04		
25	69.78	2503	1257	3	4.04		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
0.5 (CONT.)	23	76.84	2503	1384	3	4.04	B_683GH71E4
	21	83.40	2503	1502	3	4.04	
	19	90.89	2503	1637	3	4.04	
	18	99.55	2503	1793	3	3.93	
	16	109.64	2503	1974	3	3.64	
	14	126.09	2503	2271	3	3.20	
	13	136.60	2503	2460	3	2.95	
	12	150.98	2503	2719	3	2.67	
	10	176.14	2503	3172	3	2.29	
	9	196.07	2503	3531	3	2.06	
	8	215.68	2503	3884	3	1.87	
	7	243.72	2503	4389	3	1.65	
	69	25.53	4512	460	3	4.04	B_883GH71E4
	61	28.50	4512	513	3	4.04	
	57	30.87	4512	556	3	4.04	
	23	75.45	4512	1359	3	4.04	
	21	84.21	4512	1516	3	4.04	
	19	91.22	4512	1643	3	4.04	
	17	103.38	4512	1862	3	4.04	
	16	111.37	4512	2005	3	4.04	
15	120.42	4512	2168	3	4.04		
13	130.77	4512	2355	3	4.04		
12	144.58	4512	2603	3	4.01		
11	156.63	4512	2820	3	3.76		
10	176.50	4512	3178	3	3.41		
9	193.24	4512	3480	3	3.16		
8	215.25	4512	3876	3	2.88		
7	246.13	4512	4432	3	2.56		
6	272.95	4512	4915	3	2.34		
6	302.68	4512	5450	3	2.13		
0.75	310	5.65	589	153	3	2.69	B_383GH80F4
	281	6.22	589	168	3	2.69	
	242	7.22	620	195	3	2.69	
	224	7.82	620	211	3	2.69	
	198	8.85	620	239	3	2.69	
	180	9.72	620	263	3	2.69	

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
0.75 (CONT.)	163	10.72	620	290	3	2.69	B_383GH80F4
	152	11.50	617	311	3	2.69	
	138	12.65	617	342	3	2.69	
	119	14.69	617	397	3	2.69	
	110	15.91	617	430	3	2.69	
	97	17.99	726	486	3	2.69	
	88	19.78	726	534	3	2.69	
	80	21.81	726	589	3	2.69	
	72	24.16	726	653	3	2.52	
	65	26.90	726	727	3	2.34	
	61	28.72	926	776	3	2.69	
	55	31.59	926	853	3	2.59	
	48	36.69	926	991	3	2.23	
	44	39.73	926	1073	3	2.06	
	39	44.94	1150	1214	3	1.82	
	35	49.38	1150	1334	3	1.66	
	32	54.47	1150	1471	3	1.50	
	29	60.33	1150	1630	3	1.36	
	26	67.18	1150	1815	3	1.22	
	23	77.09	1411	2082	3	1.06	
	242	7.22	1032	195	3	2.69	B_483GH80F4
	208	8.40	1032	227	3	2.69	
	188	9.32	1032	252	3	2.69	
	172	10.15	1032	274	3	2.69	
	146	11.95	1110	323	3	2.69	
	126	13.90	1110	375	3	2.69	
	113	15.42	1110	417	3	2.69	
	104	16.79	1110	454	3	2.69	
93	18.78	1149	507	3	2.69		
85	20.54	1149	555	3	2.69		
78	22.54	1149	609	3	2.69		
70	24.85	1149	671	3	2.64		
64	27.55	1149	744	3	2.45		
61	28.90	1266	781	3	2.69		
52	33.60	1266	908	3	2.69		
47	37.28	1266	1007	3	2.69		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
0.75 (CONT.)	43	40.60	1266	1097	3	2.69	B_483GH80F4
	39	45.41	1591	1227	3	2.69	
	35	49.65	1591	1341	3	2.69	
	32	54.49	1591	1472	3	2.69	
	29	60.08	1591	1623	3	2.45	
	26	66.60	1591	1799	3	2.21	
	23	75.45	1878	2038	3	1.95	
	21	83.25	1878	2249	3	1.77	
	19	94.12	1878	2542	3	1.57	
	16	107.47	1878	2903	3	1.37	
	14	122.19	1878	3300	3	1.21	
	13	130.78	1878	3532	3	1.13	
	206	8.50	2503	230	3	2.69	
	184	9.52	2503	257	3	2.69	
	168	10.40	2503	281	3	2.69	
	92	18.93	2503	511	3	2.69	
	82	21.22	2503	573	3	2.69	
	76	23.16	2503	626	3	2.69	
	69	25.42	2503	687	3	2.69	
	63	27.99	2503	756	3	2.69	
	58	30.38	2503	821	3	2.69	
	34	51.96	2503	1403	3	2.69	
	30	58.23	2503	1573	3	2.69	
	28	63.57	2503	1717	3	2.69	
	25	69.78	2503	1885	3	2.69	
	23	76.84	2503	2076	3	2.69	
21	83.40	2503	2253	3	2.69		
19	90.89	2503	2455	3	2.69		
18	99.55	2503	2689	3	2.62		
16	109.64	2503	2961	3	2.43		
14	126.09	2503	3406	3	2.13		
13	136.60	2503	3690	3	1.97		
12	150.98	2503	4078	3	1.78		
10	176.14	2503	4758	3	1.53		
9	196.07	2503	5296	3	1.37		
8	215.68	2503	5826	3	1.25		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
0.75 (CONT.)	7	243.72	2503	6583	3	1.10	B_683GH80F4
	69	25.53	4512	690	3	2.69	B_883GH80F4
	61	28.50	4512	770	3	2.69	
	57	30.87	4512	834	3	2.69	
	23	75.45	4512	2038	3	2.69	
	21	84.21	4512	2275	3	2.69	
	19	91.22	4512	2464	3	2.69	
	17	103.38	4512	2792	3	2.69	
	16	111.37	4512	3008	3	2.69	
	15	120.42	4512	3253	3	2.69	
	13	130.77	4512	3532	3	2.69	
	12	144.58	4512	3905	3	2.67	
	11	156.63	4512	4231	3	2.51	
	10	176.50	4512	4767	3	2.27	
	9	193.24	4512	5220	3	2.10	
	8	215.25	4512	5814	3	1.92	
7	246.13	4512	6648	3	1.71		
6	272.95	4512	7373	3	1.56		
6	302.68	4512	8176	3	1.42		
1	310	5.65	589	203	3	2.46	B_383GH80G4
	281	6.22	589	224	3	2.46	
	242	7.22	620	260	3	2.46	
	224	7.82	620	282	3	2.45	
	198	8.85	620	319	3	2.45	
	180	9.72	620	350	3	2.46	
	163	10.72	620	386	3	2.46	
	152	11.50	617	414	3	2.46	
	138	12.65	617	456	3	2.46	
	119	14.69	617	529	3	2.46	
	110	15.91	617	573	3	2.46	
	97	17.99	726	648	3	2.46	
	88	19.78	726	712	3	2.46	
	80	21.81	726	785	3	2.46	
	72	24.16	726	870	3	2.46	
	65	26.90	726	969	3	2.28	
61	28.72	926	1034	3	2.14		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
1 (CONT.)	55	31.59	926	1138	3	1.94	B_383GH80G4
	48	36.69	926	1321	3	1.68	
	44	39.73	926	1431	3	1.55	
	39	44.94	1150	1618	3	1.37	
	35	49.38	1150	1778	3	1.24	
	32	54.47	1150	1962	3	1.13	
	29	60.33	1150	2173	3	1.02	
	242	7.22	1032	260	3	2.46	B_483GH80G4
	208	8.40	1032	303	3	2.45	
	188	9.32	1032	336	3	2.45	
	172	10.15	1032	366	3	2.45	
	146	11.95	1110	430	3	2.46	
	126	13.90	1110	501	3	2.46	
	113	15.42	1110	555	3	2.46	
	104	16.79	1110	605	3	2.46	
	93	18.78	1149	676	3	2.40	
	85	20.54	1149	740	3	2.26	
	78	22.54	1149	812	3	2.12	
	70	24.85	1149	895	3	1.98	
	64	27.55	1149	992	3	1.84	
	61	28.90	1266	1041	3	2.46	
	52	33.60	1266	1210	3	2.46	
	47	37.28	1266	1343	3	2.46	
	43	40.60	1266	1462	3	2.46	
	39	45.41	1591	1635	3	2.44	
	35	49.65	1591	1788	3	2.23	
	32	54.49	1591	1962	3	2.03	
	29	60.08	1591	2164	3	1.84	
	26	66.60	1591	2399	3	1.66	
	23	75.45	1878	2717	3	1.47	
	21	83.25	1878	2998	3	1.33	
	19	94.12	1878	3390	3	1.17	
	16	107.47	1878	3870	3	1.03	
	326	5.36	2503	193	3	2.46	B_683GH80G4
272	6.44	2503	232	3	2.46		
231	7.58	2503	273	3	2.46		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
1 (CONT.)	206	8.50	2503	306	3	2.46	B_683GH80G4
	184	9.52	2503	343	3	2.46	
	168	10.40	2503	375	3	2.45	
	147	11.94	2503	430	3	2.46	
	122	14.35	2503	517	3	2.46	
	104	16.89	2503	608	3	2.46	
	92	18.93	2503	682	3	2.46	
	82	21.22	2503	764	3	2.46	
	76	23.16	2503	834	3	2.46	
	69	25.42	2503	915	3	2.46	
	63	27.99	2503	1008	3	2.46	
	58	30.38	2503	1094	3	2.46	
	53	32.78	2503	1181	3	2.46	
	44	39.39	2503	1419	3	2.46	
	38	46.37	2503	1670	3	2.46	
	34	51.96	2503	1871	3	2.46	
	30	58.23	2503	2097	3	2.46	
	28	63.57	2503	2289	3	2.46	
	25	69.78	2503	2513	3	2.46	
	23	76.84	2503	2767	3	2.46	
	21	83.40	2503	3004	3	2.42	
	19	90.89	2503	3273	3	2.22	
	18	99.55	2503	3585	3	2.02	
	16	109.64	2503	3949	3	1.84	
	14	126.09	2503	4541	3	1.60	
	13	136.60	2503	4920	3	1.48	
	12	150.98	2503	5437	3	1.33	
	10	176.14	2503	6344	3	1.14	
	9	196.07	2503	7061	3	1.03	
	218	8.03	4512	289	3	2.46	
	186	9.41	4512	339	3	2.46	
	104	16.85	4512	607	3	2.46	
	89	19.75	4512	711	3	2.46	
74	23.54	4512	848	3	2.46		
69	25.53	4512	919	3	2.46		
61	28.50	4512	1026	3	2.46		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------

RHB-60



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
1 (CONT.)	57	30.87	4512	1112	3	2.46	B_883GH80G4
	35	49.80	4512	1794	3	2.46	
	30	58.37	4512	2102	3	2.46	
	25	69.57	4512	2506	3	2.46	
	23	75.45	4512	2717	3	2.46	
	21	84.21	4512	3033	3	2.46	
	19	91.22	4512	3285	3	2.46	
	17	103.38	4512	3723	3	2.46	
	16	111.37	4512	4011	3	2.46	
	15	120.42	4512	4337	3	2.46	
	13	130.77	4512	4710	3	2.46	
	12	144.58	4512	5207	3	2.46	
	11	156.63	4512	5641	3	2.46	
	10	176.50	4512	6357	3	2.30	
	9	193.24	4512	6959	3	2.10	
	8	215.25	4512	7752	3	1.88	
	7	246.13	4512	8864	3	1.65	
	6	272.95	4512	9830	3	1.49	
	6	302.68	4512	10901	3	1.34	
	136	12.90	5586	465	3	2.45	B_1083GH80G4
	76	23.08	5586	831	3	2.46	
	66	26.48	5586	954	3	2.46	
	56	31.25	5586	1125	3	2.46	
	52	33.87	5586	1220	3	2.46	
	29	61.22	5586	2205	3	2.46	
	25	70.24	5586	2530	3	2.46	
	21	82.90	5586	2986	3	2.46	
	19	89.85	5586	3236	3	2.46	
18	99.90	5586	3598	3	2.46		
16	108.52	5586	3908	3	2.46		
15	120.03	5586	4323	3	2.46		
14	128.86	5586	4641	3	2.46		
13	138.87	5586	5001	3	2.46		
12	150.31	5586	5413	3	2.46		
11	163.51	5586	5889	3	2.46		
10	178.90	5586	6443	3	2.46		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
1 (CONT.)	9	201.11	5586	7243	3	2.46	B_1083GH80G4
	8	219.64	5586	7910	3	2.46	
	7	243.47	5586	8768	3	2.37	
	6	278.10	5586	10016	3	2.17	
	6	307.24	5586	11065	3	2.03	
1.5	310	5.65	589	305	3	3.34	B_383GH90H4
	281	6.22	589	336	3	3.33	
	242	7.22	620	390	3	3.34	
	224	7.82	620	422	3	3.33	
	198	8.85	620	478	3	2.94	
	180	9.72	620	525	3	2.68	
	163	10.72	620	579	3	2.43	
	152	11.50	617	621	3	3.34	
	138	12.65	617	683	3	3.24	
	119	14.69	617	794	3	2.79	
	110	15.91	617	859	3	2.58	
	97	17.99	726	972	3	2.28	
	88	19.78	726	1069	3	2.07	
	80	21.81	726	1178	3	1.88	
	72	24.16	726	1305	3	1.70	
	65	26.90	726	1453	3	1.52	
	61	28.72	926	1551	3	1.43	
	55	31.59	926	1707	3	1.30	
	48	36.69	926	1982	3	1.12	
	44	39.73	926	2146	3	1.03	
	242	7.22	1032	390	3	3.34	B_483GH90H4
	208	8.40	1032	454	3	3.33	
	188	9.32	1032	503	3	3.34	
	172	10.15	1032	548	3	3.33	
	146	11.95	1110	646	3	3.33	
	126	13.90	1110	751	3	3.33	
	113	15.42	1110	833	3	3.34	
	104	16.79	1110	907	3	3.33	
	93	18.78	1149	1015	3	3.17	
	85	20.54	1149	1110	3	3.04	
78	22.54	1149	1218	3	2.90		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
1.5 (CONT.)	70	24.85	1149	1342	3	2.77	B_483GH90H4
	64	27.55	1149	1488	3	2.63	
	61	28.90	1266	1561	3	2.55	
	52	33.60	1266	1815	3	2.19	
	47	37.28	1266	2014	3	1.98	
	43	40.60	1266	2193	3	1.82	
	39	45.41	1591	2453	3	1.62	
	35	49.65	1591	2682	3	1.49	
	32	54.49	1591	2944	3	1.35	
	29	60.08	1591	3246	3	1.23	
	26	66.60	1591	3598	3	1.11	
	326	5.36	2503	290	3	3.33	B_683GH90H4
	272	6.44	2503	348	3	3.33	
	231	7.58	2503	409	3	3.34	
	206	8.50	2503	459	3	3.34	
	184	9.52	2503	514	3	3.34	
	168	10.40	2503	562	3	3.33	
	147	11.94	2503	645	3	3.34	
	122	14.35	2503	775	3	3.34	
	104	16.89	2503	912	3	3.34	
92	18.93	2503	1023	3	3.33		
82	21.22	2503	1146	3	3.34		
76	23.16	2503	1251	3	3.34		
69	25.42	2503	1373	3	3.34		
63	27.99	2503	1512	3	3.34		
58	30.38	2503	1641	3	3.34		
53	32.78	2503	1771	3	3.34		
44	39.39	2503	2128	3	3.33		
38	46.37	2503	2505	3	2.90		
34	51.96	2503	2807	3	2.59		
30	58.23	2503	3146	3	2.31		
28	63.57	2503	3434	3	2.11		
25	69.78	2503	3770	3	1.93		
23	76.84	2503	4151	3	1.75		
21	83.40	2503	4505	3	1.61		
19	90.89	2503	4910	3	1.48		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
1.5 (CONT.)	18	99.55	2503	5378	3	1.35	B_683GH90H4
	16	109.64	2503	5923	3	1.23	
	14	126.09	2503	6812	3	1.07	
	218	8.03	4512	434	3	3.33	B_883GH90H4
	186	9.41	4512	508	3	3.34	
	104	16.85	4512	910	3	3.34	
	89	19.75	4512	1067	3	3.34	
	74	23.54	4512	1272	3	3.33	
	69	25.53	4512	1379	3	3.34	
	61	28.50	4512	1540	3	3.33	
	57	30.87	4512	1668	3	3.33	
	35	49.80	4512	2690	3	3.34	
	30	58.37	4512	3153	3	3.34	
	25	69.57	4512	3758	3	3.34	
	23	75.45	4512	4076	3	3.34	
	21	84.21	4512	4549	3	3.21	
	19	91.22	4512	4928	3	2.96	
	17	103.38	4512	5585	3	2.61	
	16	111.37	4512	6016	3	2.43	
	15	120.42	4512	6505	3	2.25	
	13	130.77	4512	7064	3	2.07	
	12	144.58	4512	7810	3	1.87	
	11	156.63	4512	8461	3	1.73	
	10	176.50	4512	9535	3	1.53	
	9	193.24	4512	10439	3	1.40	
	8	215.25	4512	11628	3	1.26	
	7	246.13	4512	13296	3	1.10	
	136	12.90	5586	697	3	3.33	B_1083GH90H4
	76	23.08	5586	1247	3	3.33	
	66	26.48	5586	1430	3	3.34	
56	31.25	5586	1688	3	3.34		
52	33.87	5586	1830	3	3.34		
29	61.22	5586	3307	3	3.34		
25	70.24	5586	3794	3	3.34		
21	82.90	5586	4478	3	3.34		
19	89.85	5586	4854	3	3.34		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
1.5 (CONT.)	18	99.90	5586	5397	3	3.34	B_1083GH90H4
	16	108.52	5586	5862	3	3.34	
	15	120.03	5586	6484	3	3.34	
	14	128.86	5586	6961	3	3.34	
	13	138.87	5586	7502	3	3.22	
	12	150.31	5586	8120	3	3.09	
	11	163.51	5586	8833	3	2.95	
	10	178.90	5586	9664	3	2.75	
	9	201.11	5586	10864	3	2.44	
	8	219.64	5586	11865	3	2.24	
	7	243.47	5586	13153	3	2.02	
	6	278.10	5586	15023	3	1.77	
	6	307.24	5586	16598	3	1.60	
	65	27.02	6907	1460	3	3.33	B_1283GH90H4
	57	30.61	6907	1654	3	3.33	
	49	35.92	6907	1940	3	3.34	
	45	39.19	6907	2117	3	3.34	
	20	85.98	6907	4645	3	3.34	
	18	97.44	6907	5264	3	3.34	
	15	114.34	6907	6177	3	3.34	
	14	124.73	6907	6738	3	3.34	
	13	136.06	6907	7350	3	3.34	
	12	146.84	6907	7933	3	3.34	
	11	164.11	6907	8865	3	3.34	
	10	175.8	6907	9497	3	3.34	
9	189.04	6907	10212	3	3.21		
9	204.18	6907	11030	3	3.07		
8	221.64	6907	11973	3	2.93		
7	242.02	6907	13074	3	2.79		
6	270.90	6907	14634	3	2.62		
6	295.38	6907	15957	3	2.49		
2	310	5.65	589	407	3	2.50	B_383GH90I4
	281	6.22	589	448	3	2.50	
	242	7.22	620	520	3	2.50	
	224	7.82	620	563	3	2.49	
	198	8.85	620	637	3	2.20	

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------

RHB-65



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
2 (CONT.)	180	9.72	620	700	3	2.01	B_383GH90I4
	163	10.72	620	772	3	1.82	
	152	11.50	617	828	3	2.50	
	138	12.65	617	911	3	2.43	
	119	14.69	617	1058	3	2.09	
	110	15.91	617	1146	3	1.93	
	97	17.99	726	1296	3	1.71	
	88	19.78	726	1425	3	1.55	
	80	21.81	726	1571	3	1.41	
	72	24.16	726	1740	3	1.27	
	65	26.90	726	1938	3	1.14	
	61	28.72	926	2069	3	1.07	
	242	7.22	1032	520	3	2.50	
	208	8.40	1032	605	3	2.50	
	188	9.32	1032	671	3	2.50	
	172	10.15	1032	731	3	2.49	
	146	11.95	1110	861	3	2.50	
	126	13.90	1110	1001	3	2.50	
	113	15.42	1110	1111	3	2.50	
	104	16.79	1110	1209	3	2.50	
	93	18.78	1149	1353	3	2.38	
	85	20.54	1149	1479	3	2.28	
	78	22.54	1149	1624	3	2.18	
	70	24.85	1149	1790	3	2.08	
	64	27.55	1149	1984	3	1.97	
	61	28.90	1266	2082	3	1.91	
	52	33.60	1266	2420	3	1.65	
	47	37.28	1266	2685	3	1.48	
	43	40.60	1266	2924	3	1.36	
	39	45.41	1591	3271	3	1.22	
	35	49.65	1591	3576	3	1.11	
	32	54.49	1591	3925	3	1.01	
	326	5.36	2503	386	3	2.50	B_683GH90I4
272	6.44	2503	464	3	2.50		
231	7.58	2503	546	3	2.50		
206	8.50	2503	612	3	2.50		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER	
2 (CONT.)	184	9.52	2503	686	3	2.50	B_683GH90I4	
	168	10.40	2503	749	3	2.50		
	147	11.94	2503	860	3	2.50		
	122	14.35	2503	1034	3	2.50		
	104	16.89	2503	1217	3	2.50		
	92	18.93	2503	1364	3	2.50		
	82	21.22	2503	1528	3	2.50		
	76	23.16	2503	1668	3	2.50		
	69	25.42	2503	1831	3	2.50		
	63	27.99	2503	2016	3	2.50		
	58	30.38	2503	2188	3	2.50		
	53	32.78	2503	2361	3	2.50		
	44	39.39	2503	2837	3	2.50		
	38	46.37	2503	3340	3	2.17		
	34	51.96	2503	3743	3	1.94		
	30	58.23	2503	4194	3	1.73		
	28	63.57	2503	4579	3	1.59		
	25	69.78	2503	5026	3	1.44		
	23	76.84	2503	5535	3	1.31		
	21	83.40	2503	6007	3	1.21		
	19	90.89	2503	6547	3	1.11		
	18	99.55	2503	7170	3	1.01		
	218	8.03	4512	4512	578	3	2.50	B_883GH90I4
	186	9.41	4512	4512	678	3	2.50	
	104	16.85	4512	4512	1214	3	2.50	
	89	19.75	4512	4512	1423	3	2.50	
	74	23.54	4512	4512	1696	3	2.50	
	69	25.53	4512	4512	1839	3	2.50	
61	28.50	4512	4512	2053	3	2.50		
57	30.87	4512	4512	2224	3	2.50		
35	49.80	4512	4512	3587	3	2.50		
30	58.37	4512	4512	4204	3	2.50		
25	69.57	4512	4512	5011	3	2.50		
23	75.45	4512	4512	5435	3	2.50		
21	84.21	4512	4512	6066	3	2.41		
19	91.22	4512	4512	6570	3	2.22		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
2 (CONT.)	17	103.38	4512	7446	3	1.96	B_883GH90I4
	16	111.37	4512	8022	3	1.82	
	15	120.42	4512	8674	3	1.68	
	13	130.77	4512	9419	3	1.55	
	12	144.58	4512	10414	3	1.40	
	11	156.63	4512	11282	3	1.29	
	10	176.50	4512	12713	3	1.15	
	9	193.24	4512	13919	3	1.05	
	136	12.90	5586	929	3	2.50	
	76	23.08	5586	1662	3	2.50	
	66	26.48	5586	1907	3	2.50	
	56	31.25	5586	2251	3	2.50	
	52	33.87	5586	2440	3	2.50	
	29	61.22	5586	4410	3	2.50	
	25	70.24	5586	5059	3	2.50	
	21	82.90	5586	5971	3	2.50	
	19	89.85	5586	6472	3	2.50	
	18	99.90	5586	7196	3	2.50	
	16	108.52	5586	7817	3	2.50	
	15	120.03	5586	8646	3	2.50	
	14	128.86	5586	9282	3	2.50	
	13	138.87	5586	10003	3	2.42	
	12	150.31	5586	10827	3	2.31	
	11	163.51	5586	11777	3	2.21	
	10	178.90	5586	12886	3	2.06	
	9	201.11	5586	14486	3	1.83	
	8	219.64	5586	15820	3	1.68	
	7	243.47	5586	17537	3	1.51	
	6	278.10	5586	20031	3	1.33	
	6	307.24	5586	22130	3	1.20	
	65	27.02	6907	1946	3	2.50	B_1283GH90I4
	57	30.61	6907	2205	3	2.50	
	49	35.92	6907	2587	3	2.50	
	45	39.19	6907	2823	3	2.50	
	20	85.98	6907	6193	3	2.50	
	18	97.44	6907	7018	3	2.50	

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
2 (CONT.)	15	114.34	6907	8236	3	2.50	B_1283GH90I4
	14	124.73	6907	8984	3	2.50	
	13	136.06	6907	9800	3	2.50	
	12	146.84	6907	10577	3	2.50	
	11	164.11	6907	11821	3	2.50	
	10	175.80	6907	12663	3	2.50	
	9	189.04	6907	13616	3	2.41	
	9	204.18	6907	14707	3	2.30	
	8	221.64	6907	15964	3	2.20	
	7	242.02	6907	17432	3	2.09	
	6	270.90	6907	19513	3	1.96	
6	295.38	6907	21276	3	1.87		
3	310	5.65	589	610	3	1.87	B_383GH100J4
	281	6.22	589	672	3	1.75	
	242	7.22	620	780	3	1.59	
	224	7.82	620	845	3	1.50	
	198	8.85	620	956	3	1.38	
	180	9.72	620	1050	3	1.30	
	163	10.72	620	1158	3	1.21	
	152	11.50	617	1242	3	1.78	
	138	12.65	617	1367	3	1.62	
	119	14.69	617	1587	3	1.39	
	110	15.91	617	1719	3	1.29	
	97	17.99	726	1944	3	1.14	
	88	19.78	726	2137	3	1.04	
	242	7.22	1032	780	3	3.30	B_483GH100J4
	208	8.40	1032	908	3	2.83	
	188	9.32	1032	1007	3	2.55	
	172	10.15	1032	1097	3	2.34	
	146	11.95	1110	1291	3	2.90	
	126	13.90	1110	1502	3	2.61	
113	15.42	1110	1666	3	2.39		
104	16.79	1110	1814	3	2.20		
93	18.78	1149	2029	3	1.96		
85	20.54	1149	2219	3	1.79		
78	22.54	1149	2435	3	1.64		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
3 (CONT.)	70	24.85	1149	2685	3	1.48	B_483GH100J4
	64	27.55	1149	2977	3	1.34	
	61	28.90	1266	3122	3	1.28	
	52	33.60	1266	3630	3	1.10	
	326	5.36	2503	579	3	3.45	B_683GH100J4
	272	6.44	2503	696	3	3.45	
	231	7.58	2503	819	3	3.45	
	206	8.50	2503	918	3	3.45	
	184	9.52	2503	1029	3	3.45	
	168	10.40	2503	1124	3	3.45	
	147	11.94	2503	1290	3	3.45	
	122	14.35	2503	1550	3	3.45	
	104	16.89	2503	1825	3	3.45	
	92	18.93	2503	2045	3	3.31	
	82	21.22	2503	2293	3	3.05	
	76	23.16	2503	2502	3	2.87	
	69	25.42	2503	2746	3	2.64	
	63	27.99	2503	3024	3	2.40	
	58	30.38	2503	3282	3	2.21	
	53	32.78	2503	3542	3	1.98	
	44	39.39	2503	4256	3	1.71	
	38	46.37	2503	5010	3	1.45	
	34	51.96	2503	5614	3	1.29	
	30	58.23	2503	6291	3	1.15	
	28	63.57	2503	6868	3	1.06	
	316	5.54	4505	599	3	3.45	B_883GH100J4
	262	6.69	4505	723	3	3.45	
	218	8.03	4512	868	3	3.45	
	186	9.41	4512	1017	3	3.45	
	150	11.64	4512	1258	3	3.45	
	125	14.04	4512	1517	3	3.45	
	104	16.85	4512	1821	3	3.45	
	89	19.75	4512	2134	3	3.45	
74	23.54	4512	2543	3	3.45		
69	25.53	4512	2758	3	3.45		
61	28.50	4512	3079	3	3.31		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
3 (CONT.)	57	30.87	4512	3335	3	3.19	B_883GH100J4
	51	34.40	4512	3717	3	3.45	
	42	41.50	4512	4484	3	3.26	
	35	49.80	4512	5381	3	2.71	
	30	58.37	4512	6306	3	2.32	
	25	69.57	4512	7517	3	1.94	
	23	75.45	4512	8152	3	1.79	
	21	84.21	4512	9098	3	1.61	
	19	91.22	4512	9856	3	1.48	
	17	103.38	4512	11169	3	1.31	
	16	111.37	4512	12033	3	1.21	
	15	120.42	4512	13011	3	1.12	
	13	130.77	4512	14129	3	1.03	
	187	9.36	5586	1011	3	3.45	B_1083GH100J4
	160	10.97	5586	1185	3	3.45	
	136	12.90	5586	1394	3	3.45	
	104	16.75	5586	1810	3	3.45	
	89	19.63	5586	2121	3	3.45	
	76	23.08	5586	2494	3	3.45	
	66	26.48	5586	2861	3	3.45	
56	31.25	5586	3376	3	3.45		
52	33.87	5586	3659	3	3.45		
39	44.44	5586	4801	3	3.45		
34	52.08	5586	5627	3	3.45		
29	61.22	5586	6614	3	3.45		
25	70.24	5586	7589	3	3.45		
21	82.90	5586	8957	3	2.96		
19	89.85	5586	9708	3	2.74		
18	99.90	5586	10793	3	2.46		
16	108.52	5586	11725	3	2.26		
15	120.03	5586	12968	3	2.05		
14	128.86	5586	13922	3	1.91		
13	138.87	5586	15004	3	1.77		
12	150.31	5586	16240	3	1.64		
11	163.51	5586	17666	3	1.50		
10	178.90	5586	19329	3	1.37		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
3 (CONT.)	9	201.11	5586	21728	3	1.22	B_1083GH100J4
	8	219.64	5586	23731	3	1.12	
	7	243.47	5586	26305	3	1.01	
	161	10.88	6907	1176	3	3.45	B_1283GH100J4
	139	12.56	6907	1357	3	3.45	
	88	19.92	6907	2152	3	3.45	
	76	22.99	6907	2484	3	3.45	
	65	27.02	6907	2919	3	3.45	
	57	30.61	6907	3307	3	3.45	
	49	35.92	6907	3881	3	3.45	
	45	39.19	6907	4234	3	3.45	
	28	63.41	6907	6851	3	3.45	
	24	73.18	6907	7907	3	3.45	
	20	85.98	6907	9290	3	3.45	
	18	97.44	6907	10528	3	3.45	
	15	114.34	6907	12354	3	3.37	
	14	124.73	6907	13476	3	3.09	
	13	136.06	6907	14700	3	2.83	
	12	146.84	6907	15865	3	2.62	
	11	164.11	6907	17731	3	2.35	
	10	175.80	6907	18994	3	2.19	
	9	189.04	6907	20424	3	2.04	
	9	204.18	6907	22060	3	1.89	
	8	221.64	6907	23947	3	1.74	
	7	242.02	6907	26149	3	1.59	
	6	270.90	6907	29269	3	1.42	
	6	295.38	6907	31914	3	1.30	
	75	23.19	11951	2506	3	3.45	B_1483GH100J4
	66	26.58	11951	2872	3	3.45	
	24	73.80	13027	7974	3	3.45	
21	84.61	13027	9142	3	3.45		
17	101.53	13027	10970	3	3.45		
16	112.35	13027	12139	3	3.45		
13	131.49	13027	14207	3	3.45		
12	142.41	13027	15386	3	3.36		
11	158.93	13027	17171	3	3.25		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER	
3 (CONT.)	10	168.50	13027	18205	3	3.13	B_1483GH100J4	
	9	191.02	13027	20638	3	3.01		
	9	204.38	13027	22082	3	2.85		
	8	214.96	13027	23225	3	2.73		
	8	231.95	13027	25061	3	2.55		
	7	251.55	13027	27178	3	2.38		
	6	274.42	13027	29649	3	2.21		
	6	306.08	13027	33070	3	2.00		
5	326	5.36	2503	965	3	2.77	B_683GH112L4	
	272	6.44	2503	1160	3	2.77		
	231	7.58	2503	1365	3	2.77		
	206	8.50	2503	1531	3	2.77		
	184	9.52	2503	1714	3	2.75		
	168	10.40	2503	1873	3	2.59		
	147	11.94	2503	2150	3	2.74		
	122	14.35	2503	2584	3	2.41		
	104	16.89	2503	3041	3	2.15		
	92	18.93	2503	3409	3	1.98		
	82	21.22	2503	3821	3	1.83		
	76	23.16	2503	4170	3	1.72		
	69	25.42	2503	4577	3	1.59		
	63	27.99	2503	5040	3	1.44		
	58	30.38	2503	5471	3	1.33		
	53	32.78	2503	5903	3	1.19		
	44	39.39	2503	7093	3	1.02		
		316	5.54	4505	998	3	2.77	B_883GH112L4
		262	6.69	4505	1205	3	2.77	
		218	8.03	4512	1446	3	2.77	
186		9.41	4512	1694	3	2.77		
150		11.64	4512	2096	3	2.77		
125		14.04	4512	2528	3	2.77		
104		16.85	4512	3034	3	2.77		
89		19.75	4512	3556	3	2.77		
74		23.54	4512	4239	3	2.75		
69		25.53	4512	4597	3	2.65		
61	28.50	4512	5132	3	2.51			

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
5 (CONT.)	57	30.87	4512	5559	3	2.42	B_883GH112L4
	51	34.40	4512	6194	3	2.36	
	42	41.50	4512	7473	3	1.95	
	35	49.80	4512	8968	3	1.63	
	30	58.37	4512	10511	3	1.39	
	25	69.57	4512	12528	3	1.17	
	23	75.45	4512	13586	3	1.07	
	228	7.68	5586	1383	3	2.77	B_1083GH112L4
	187	9.36	5586	1685	3	2.78	
	160	10.97	5586	1975	3	2.77	
	136	12.90	5586	2323	3	2.77	
	127	13.74	5586	2474	3	2.77	
	104	16.75	5586	3016	3	2.77	
	89	19.63	5586	3535	3	2.77	
	76	23.08	5586	4156	3	2.77	
	66	26.48	5586	4768	3	2.77	
	56	31.25	5586	5627	3	2.77	
	52	33.87	5586	6099	3	2.77	
	48	36.44	5586	6562	3	2.77	
	39	44.44	5586	8002	3	2.77	
	34	52.08	5586	9378	3	2.77	
	29	61.22	5586	11024	3	2.41	
	25	70.24	5586	12648	3	2.10	
	21	82.90	5586	14928	3	1.78	
	19	89.85	5586	16179	3	1.64	
	18	99.90	5586	17989	3	1.48	
	16	108.52	5586	19541	3	1.36	
	15	120.03	5586	21614	3	1.23	
	14	128.86	5586	23204	3	1.14	
	13	138.87	5586	25007	3	1.06	
191	9.16	6907	1649	3	2.77	B_1283GH112L4	
161	10.88	6907	1959	3	2.77		
139	12.56	6907	2262	3	2.77		
104	16.76	6907	3018	3	2.77		
88	19.92	6907	3587	3	2.77		
76	22.99	6907	4140	3	2.77		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
5 (CONT.)	65	27.02	6907	4866	3	2.77	B_1283GH112L4
	57	30.61	6907	5512	3	2.77	
	49	35.92	6907	6468	3	2.77	
	45	39.19	6907	7057	3	2.77	
	33	53.36	6907	9609	3	2.77	
	28	63.41	6907	11418	3	2.77	
	24	73.18	6907	13178	3	2.77	
	20	85.98	6907	15483	3	2.69	
	18	97.44	6907	17546	3	2.37	
	15	114.34	6907	20589	3	2.02	
	14	124.73	6907	22460	3	1.85	
	13	136.06	6907	24501	3	1.70	
	12	146.84	6907	26442	3	1.57	
	11	164.11	6907	29552	3	1.41	
	10	175.80	6907	31657	3	1.31	
	9	189.04	6907	34041	3	1.22	
	9	204.18	6907	36767	3	1.13	
	8	221.64	6907	39911	3	1.04	
	88	19.84	11951	3573	3	2.77	B_1483GH112L4
	75	23.19	11951	4176	3	2.77	
	66	26.58	11951	4786	3	2.77	
	57	30.74	12561	5535	3	2.77	
	28	63.16	13027	11373	3	2.77	
	24	73.80	13027	13289	3	2.77	
	21	84.61	13027	15236	3	2.77	
	18	97.82	13027	17615	3	2.77	
	17	101.53	13027	18283	3	2.77	
	16	112.35	13027	20231	3	2.77	
13	131.49	13027	23678	3	2.69		
12	142.41	13027	25644	3	2.54		
11	158.93	13027	28619	3	2.46		
10	168.50	13027	30342	3	2.33		
9	191.02	13027	34397	3	2.06		
9	204.38	13027	36803	3	1.92		
8	214.96	13027	38708	3	1.83		
8	231.95	13027	41768	3	1.70		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------

RHB-75



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
5 (CONT.)	7	251.55	13027	45297	3	1.56	B_1483GH112L4
	6	274.42	13027	49415	3	1.43	
	6	306.08	13027	55116	3	1.28	
7.5	316	5.54	4505	1496	3	3.59	B_883GH132M4
	262	6.69	4505	1807	3	3.38	
	218	8.03	4512	2169	3	3.16	
	186	9.41	4512	2542	3	2.96	
	150	11.64	4512	3144	3	3.59	
	125	14.04	4512	3792	3	3.32	
	104	16.85	4512	4551	3	2.92	
	89	19.75	4512	5335	3	2.61	
	74	23.54	4512	6358	3	2.30	
	69	25.53	4512	6896	3	2.12	
	61	28.50	4512	7698	3	1.90	
	57	30.87	4512	8338	3	1.75	
	51	34.40	4512	9292	3	1.57	
	42	41.50	4512	11209	3	1.30	
	35	49.80	4512	13451	3	1.09	
	228	7.68	5586	2074	3	4.02	B_1083GH132M4
	187	9.36	5586	2528	3	3.82	
	160	10.97	5586	2963	3	3.62	
	136	12.90	5586	3484	3	3.41	
	127	13.74	5586	3711	3	4.02	
	104	16.75	5586	4524	3	3.82	
	89	19.63	5586	5302	3	3.62	
	76	23.08	5586	6234	3	3.41	
	66	26.48	5586	7152	3	3.21	
	56	31.25	5586	8441	3	2.97	
	52	33.87	5586	9149	3	2.76	
	48	36.44	5586	9843	3	2.56	
39	44.44	5586	12004	3	2.21		
34	52.08	5586	14067	3	1.89		
29	61.22	5586	16536	3	1.61		
25	70.24	5586	18972	3	1.40		
21	82.90	5586	22392	3	1.19		
19	89.85	5586	24269	3	1.09		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER	
7.5 (CONT.)	246	7.10	6907	1918	3	4.37	B_1283GH132M4	
	212	8.26	6907	2231	3	4.37		
	191	9.16	6907	2474	3	4.36		
	161	10.88	6907	2939	3	4.37		
	139	12.56	6907	3393	3	4.36		
	135	13.00	6907	3511	3	4.37		
	116	15.13	6907	4087	3	4.36		
	104	16.76	6907	4527	3	4.37		
	88	19.92	6907	5381	3	4.37		
	76	22.99	6907	6210	3	4.37		
	65	27.02	6907	7298	3	4.25		
	57	30.61	6907	8268	3	4.07		
	49	35.92	6907	9702	3	3.84		
	45	39.19	6907	10585	3	3.71		
	42	41.38	6907	11177	3	3.72		
	36	48.14	6907	13003	3	3.20		
	33	53.36	6907	14413	3	2.89		
	28	63.41	6907	17127	3	2.43		
	24	73.18	6907	19766	3	2.10		
	20	85.98	6907	23224	3	1.79		
	18	97.44	6907	26319	3	1.58		
	15	114.34	6907	30884	3	1.35		
	14	124.73	6907	33690	3	1.23		
	13	136.06	6907	36751	3	1.13		
	12	146.84	6907	39663	3	1.05		
		235	7.44	10246	2010	3	4.37	B_1483GH132M4
		199	8.79	10246	2374	3	4.36	
		116	15.05	11162	4065	3	4.37	
	98	17.77	11951	4800	3	4.37		
	88	19.84	11951	5359	3	4.37		
	75	23.19	11951	6264	3	4.25		
	66	26.58	11951	7179	3	4.07		
	57	30.74	12561	8303	3	3.84		
	56	31.10	12561	8400	3	4.37		
	42	41.38	12561	11177	3	4.37		
	37	47.91	13027	12941	3	4.37		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
7.5 (CONT.)	31	56.57	13027	15280	3	4.37	B_1483GH132M4
	28	63.16	13027	17060	3	4.15	
	24	73.80	13027	19934	3	3.55	
	21	84.61	13027	22854	3	3.10	
	18	97.82	13027	26422	3	2.68	
	17	101.53	13027	27424	3	2.58	
	16	112.35	13027	30347	3	2.33	
	13	131.49	13027	35516	3	1.99	
	12	142.41	13027	38466	3	1.84	
	11	158.93	13027	42928	3	1.65	
	10	168.5	13027	45513	3	1.56	
	9	191.02	13027	51596	3	1.37	
	9	204.38	13027	55204	3	1.28	
	8	214.96	13027	58062	3	1.22	
	8	231.95	13027	62651	3	1.13	
	7	251.55	13027	67945	3	1.04	
	172	10.17	15278	2747	3	4.37	B_1683GH132M4
	150	11.67	16566	3152	3	4.37	
	92	19.09	17607	5156	3	4.37	
	80	21.90	17607	5915	3	4.37	
	72	24.14	17607	6520	3	4.37	
	61	28.54	18949	7709	3	4.25	
	54	32.53	18949	8787	3	4.07	
	33	53.18	18949	14364	3	4.36	
	29	60.99	18949	16474	3	4.37	
	26	67.22	18949	18157	3	4.37	
	22	79.49	18949	21471	3	4.25	
	19	90.60	18949	24472	3	4.07	
	17	104.18	18949	28140	3	3.84	
	15	119.09	18949	32167	3	3.71	
13	138.00	18949	37275	3	3.21		
12	150.36	18949	40613	3	2.94		
10	167.50	18949	45243	3	2.64		
10	177.43	18949	47925	3	2.49		
9	199.54	18949	53897	3	2.22		
8	213.33	18949	57622	3	2.07		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
7.5 (CONT.)	8	226.15	18949	61085	3	1.96	B_1683GH132M4
	7	243.80	18949	65852	3	1.81	
	7	264.18	18949	71357	3	1.67	
	6	287.95	18949	77777	3	1.35	
10	316	5.54	4505	1995	3	2.69	B_883GH132N4
	262	6.69	4505	2409	3	2.54	
	218	8.03	4512	2892	3	2.37	
	186	9.41	4512	3389	3	2.22	
	150	11.64	4512	4192	3	2.69	
	125	14.04	4512	5056	3	2.49	
	104	16.85	4512	6068	3	2.19	
	89	19.75	4512	7113	3	1.96	
	74	23.54	4512	8478	3	1.72	
	69	25.53	4512	9194	3	1.59	
	61	28.50	4512	10264	3	1.42	
	57	30.87	4512	11118	3	1.31	
	51	34.40	4512	12389	3	1.18	
	228	7.68	5586	2766	3	3.02	B_1083GH132N4
	187	9.36	5586	3371	3	2.86	
	160	10.97	5586	3951	3	2.72	
	136	12.90	5586	4646	3	2.55	
	127	13.74	5586	4948	3	3.02	
	104	16.75	5586	6032	3	2.86	
	89	19.63	5586	7070	3	2.72	
	76	23.08	5586	8312	3	2.55	
	66	26.48	5586	9537	3	2.41	
	56	31.25	5586	11254	3	2.23	
	52	33.87	5586	12198	3	2.07	
	48	36.44	5586	13124	3	1.92	
	39	44.44	5586	16005	3	1.66	
	34	52.08	5586	18756	3	1.42	
	29	61.22	5586	22048	3	1.20	
25	70.24	5586	25296	3	1.05		
246	7.10	6907	2557	3	3.27	B_1283GH132N4	
212	8.26	6907	2975	3	3.27		
191	9.16	6907	3299	3	3.27		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
10 (CONT.)	161	10.88	6907	3918	3	3.27	B_1283GH132N4
	139	12.56	6907	4523	3	3.27	
	135	13.00	6907	4682	3	3.27	
	116	15.13	6907	5449	3	3.27	
	104	16.76	6907	6036	3	3.27	
	88	19.92	6907	7174	3	3.27	
	76	22.99	6907	8280	3	3.27	
	65	27.02	6907	9731	3	3.18	
	57	30.61	6907	11024	3	3.05	
	49	35.92	6907	12936	3	2.88	
	45	39.19	6907	14114	3	2.78	
	42	41.38	6907	14903	3	2.79	
	36	48.14	6907	17337	3	2.40	
	33	53.36	6907	19217	3	2.16	
	28	63.41	6907	22837	3	1.82	
	24	73.18	6907	26355	3	1.58	
	20	85.98	6907	30965	3	1.34	
	18	97.44	6907	35092	3	1.19	
	15	114.34	6907	41179	3	1.01	
	235	7.44	10246	2679	3	3.28	
	199	8.79	10246	3166	3	3.27	
	116	15.05	11162	5420	3	3.27	
	98	17.77	11951	6400	3	3.27	
	88	19.84	11951	7145	3	3.27	
	75	23.19	11951	8352	3	3.19	
	66	26.58	11951	9573	3	3.05	
	57	30.74	12561	11071	3	2.88	
	56	31.10	12561	11200	3	3.27	
	42	41.38	12561	14903	3	3.27	
	37	47.91	13027	17254	3	3.27	
	31	56.57	13027	20373	3	3.27	
	28	63.16	13027	22747	3	3.11	
	24	73.80	13027	26579	3	2.66	
	21	84.61	13027	30472	3	2.32	
18	97.82	13027	35229	3	2.01		
17	101.53	13027	36565	3	1.94		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
10 (CONT.)	16	112.35	13027	40462	3	1.75	B_1483GH132N4
	13	131.49	13027	47355	3	1.50	
	12	142.41	13027	51288	3	1.38	
	11	158.93	13027	57238	3	1.24	
	10	168.50	13027	60684	3	1.17	
	9	191.02	13027	68794	3	1.03	
	172	10.17	15278	3663	3	3.27	B_1683GH132N4
	150	11.67	16566	4203	3	3.27	
	92	19.09	17607	6875	3	3.27	
	80	21.90	17607	7887	3	3.27	
	72	24.14	17607	8694	3	3.27	
	61	28.54	18949	10278	3	3.19	
	54	32.53	18949	11715	3	3.05	
	33	53.18	18949	19152	3	3.27	
	29	60.99	18949	21965	3	3.27	
	26	67.22	18949	24209	3	3.27	
	22	79.49	18949	28628	3	3.19	
	19	90.60	18949	32629	3	3.05	
	17	104.18	18949	37520	3	2.88	
	15	119.09	18949	42889	3	2.78	
	13	138.00	18949	49700	3	2.40	
	12	150.36	18949	54151	3	2.21	
	10	167.50	18949	60324	3	1.98	
	10	177.43	18949	63900	3	1.87	
	9	199.54	18949	71863	3	1.66	
	8	213.33	18949	76829	3	1.56	
8	226.15	18949	81446	3	1.47		
7	243.80	18949	87803	3	1.36		
7	264.18	18949	95143	3	1.26		
6	287.95	18949	103703	3	1.01		
15	228	7.68	5586	4149	3	3.02	B_1083GH160P4
	187	9.36	5586	5056	3	2.51	
	160	10.97	5586	5926	3	2.17	
	136	12.90	5586	6969	3	1.87	
	127	13.74	5586	7423	3	2.85	
	104	16.75	5586	9049	3	2.48	

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
15 (CONT.)	89	19.63	5586	10604	3	2.22	B_1083GH160P4
	76	23.08	5586	12468	3	1.97	
	66	26.48	5586	14305	3	1.73	
	56	31.25	5586	16882	3	1.49	
	52	33.87	5586	18297	3	1.38	
	48	36.44	5586	19685	3	1.28	
	39	44.44	5586	24007	3	1.11	
	246	7.10	6907	3836	3	3.03	B_1283GH160P4
	212	8.26	6907	4462	3	3.03	
	191	9.16	6907	4948	3	3.03	
	161	10.88	6907	5878	3	3.03	
	139	12.56	6907	6785	3	2.90	
	135	13.00	6907	7023	3	3.03	
	116	15.13	6907	8173	3	3.03	
	104	16.76	6907	9054	3	3.03	
	88	19.92	6907	10761	3	3.03	
	76	22.99	6907	12420	3	2.90	
	65	27.02	6907	14597	3	2.69	
	57	30.61	6907	16536	3	2.50	
	49	35.92	6907	19404	3	2.14	
	45	39.19	6907	21171	3	1.96	
	42	41.38	6907	22354	3	1.86	
	36	48.14	6907	26006	3	1.60	
	33	53.36	6907	28826	3	1.44	
	28	63.41	6907	34255	3	1.21	
	24	73.18	6907	39533	3	1.05	
	362	4.83	9207	2609	3	3.03	B_1483GH160P4
	272	6.43	9207	3474	3	3.03	
	235	7.44	10246	4019	3	3.03	
	199	8.79	10246	4748	3	3.03	
	179	9.77	10246	5278	3	3.03	
	135	13.00	11162	7023	3	3.03	
	116	15.05	11162	8130	3	3.03	
	98	17.77	11951	9600	3	3.03	
	88	19.84	11951	10718	3	2.90	
	75	23.19	11951	12528	3	2.69	

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
15 (CONT.)	66	26.58	11951	14359	3	2.54	B_1483GH160P4
	57	30.74	12561	16606	3	2.36	
	56	31.10	12561	16801	3	3.03	
	42	41.38	12561	22354	3	2.81	
	37	47.91	13027	25882	3	2.74	
	31	56.57	13027	30560	3	2.32	
	28	63.16	13027	34120	3	2.08	
	24	73.80	13027	39868	3	1.78	
	21	84.61	13027	45708	3	1.55	
	18	97.82	13027	52844	3	1.34	
	17	101.53	13027	54848	3	1.29	
	16	112.35	13027	60693	3	1.17	
	13	131.49	13027	71033	3	1.00	
	265	6.61	13774	3571	3	3.03	B_1683GH160P4
	203	8.64	15278	4667	3	3.03	
	172	10.17	15278	5494	3	3.03	
	150	11.67	16566	6304	3	3.03	
	141	12.41	16566	6704	3	3.03	
	108	16.21	16566	8757	3	3.03	
	92	19.09	17607	10313	3	3.03	
80	21.90	17607	11831	3	3.03		
72	24.14	17607	13041	3	2.90		
61	28.54	18949	15418	3	2.69		
54	32.53	18949	17573	3	2.54		
51	34.55	18949	18664	3	3.03		
39	45.15	18949	24391	3	3.03		
33	53.18	18949	28729	3	3.03		
29	60.99	18949	32948	3	3.03		
26	67.22	18949	36313	3	2.90		
22	79.49	18949	42942	3	2.69		
19	90.60	18949	48943	3	2.44		
17	104.18	18949	56280	3	2.12		
15	119.09	18949	64334	3	1.86		
13	138.00	18949	74550	3	1.60		
12	150.36	18949	81227	3	1.47		
10	167.50	18949	90486	3	1.32		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
15 (CONT.)	10	177.43	18949	95850	3	1.25	B_1683GH160P4
	9	199.54	18949	107794	3	1.11	
	8	213.33	18949	115244	3	1.04	
20	228	7.68	5586	5532	3	2.27	B_1083GH160Q4
	187	9.36	5586	6742	3	1.89	
	160	10.97	5586	7902	3	1.63	
	136	12.90	5586	9292	3	1.40	
	127	13.74	5586	9897	3	2.13	
	104	16.75	5586	12065	3	1.86	
	89	19.63	5586	14139	3	1.66	
	76	23.08	5586	16624	3	1.48	
	66	26.48	5586	19073	3	1.30	
	56	31.25	5586	22509	3	1.11	
	52	33.87	5586	24396	3	1.03	
	246	7.10	6907	5114	3	2.27	B_1283GH160Q4
	212	8.26	6907	5950	3	2.27	
	191	9.16	6907	6598	3	2.27	
	161	10.88	6907	7837	3	2.27	
	139	12.56	6907	9047	3	2.18	
	135	13.00	6907	9364	3	2.27	
	116	15.13	6907	10898	3	2.27	
	104	16.76	6907	12072	3	2.27	
	88	19.92	6907	14348	3	2.27	
	76	22.99	6907	16559	3	2.18	
	65	27.02	6907	19462	3	2.02	
	57	30.61	6907	22048	3	1.88	
	49	35.92	6907	25873	3	1.61	
	45	39.19	6907	28228	3	1.47	
	42	41.38	6907	29805	3	1.40	
	36	48.14	6907	34675	3	1.20	
	33	53.36	6907	38434	3	1.08	
	362	4.83	9207	3479	3	2.27	B_1483GH160Q4
	272	6.43	9207	4631	3	2.27	
	235	7.44	10246	5359	3	2.27	
	199	8.79	10246	6331	3	2.27	
	179	9.77	10246	7037	3	2.27	

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
20 (CONT.)	135	13.00	11162	9364	3	2.27	B_1483GH160Q4
	116	15.05	11162	10840	3	2.27	
	98	17.77	11951	12799	3	2.27	
	88	19.84	11951	14290	3	2.18	
	75	23.19	11951	16703	3	2.02	
	66	26.58	11951	19145	3	1.90	
	57	30.74	12561	22142	3	1.77	
	56	31.10	12561	22401	3	2.27	
	42	41.38	12561	29805	3	2.10	
	37	47.91	13027	34509	3	2.05	
	31	56.57	13027	40747	3	1.74	
	28	63.16	13027	45493	3	1.56	
	24	73.80	13027	53157	3	1.33	
	21	84.61	13027	60943	3	1.16	
	18	97.82	13027	70458	3	1.00	
	265	6.61	13774	4761	3	2.27	B_1683GH160Q4
	203	8.64	15278	6223	3	2.27	
	172	10.17	15278	7325	3	2.27	
	150	11.67	16566	8406	3	2.27	
	141	12.41	16566	8939	3	2.27	
	108	16.21	16566	11676	3	2.27	
	92	19.09	17607	13750	3	2.27	
	80	21.90	17607	15774	3	2.27	
	72	24.14	17607	17388	3	2.18	
	61	28.54	18949	20557	3	2.02	
	54	32.53	18949	23431	3	1.90	
	51	34.55	18949	24886	3	2.27	
	39	45.15	18949	32521	3	2.27	
33	53.18	18949	38305	3	2.27		
29	60.99	18949	43930	3	2.27		
26	67.22	18949	48418	3	2.18		
22	79.49	18949	57256	3	2.02		
19	90.60	18949	65258	3	1.83		
17	104.18	18949	75039	3	1.59		
15	119.09	18949	85779	3	1.39		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
20 (CONT)	13	138.00	18949	99399	3	1.20	B_1683GH160Q4
	12	150.36	18949	108302	3	1.10	
25	246	7.10	6907	6393	3	3.70	B_1283GH180R4
	212	8.26	6907	7437	3	3.42	
	191	9.16	6907	8247	3	3.13	
	161	10.88	6907	9796	3	2.69	
	139	12.56	6907	11308	3	2.37	
	135	13.00	6907	11705	3	3.01	
	116	15.13	6907	13622	3	2.71	
	104	16.76	6907	15090	3	2.52	
	88	19.92	6907	17935	3	2.23	
	76	22.99	6907	20699	3	1.96	
	65	27.02	6907	24328	3	1.69	
	57	30.61	6907	27560	3	1.50	
	49	35.92	6907	32341	3	1.29	
	45	39.19	6907	35285	3	1.18	
	42	41.38	6907	37257	3	1.12	
	362	4.83	9207	4349	3	3.70	
	272	6.43	9207	5789	3	3.70	
	235	7.44	10246	6699	3	3.71	
	199	8.79	10246	7914	3	3.67	
	179	9.77	10246	8796	3	3.70	
	135	13.00	11162	11705	3	3.70	
	116	15.05	11162	13550	3	3.71	
	98	17.77	11951	15999	3	3.67	
	88	19.84	11951	17863	3	3.49	
	75	23.19	11951	20879	3	3.24	
	66	26.58	11951	23931	3	2.86	
	57	30.74	12561	27677	3	2.50	
	56	31.10	12561	28001	3	2.53	
	42	41.38	12561	37257	3	1.90	
	37	47.91	13027	43136	3	1.64	
	31	56.57	13027	50933	3	1.39	
	28	63.16	13027	56867	3	1.25	
24	73.80	13027	66446	3	1.07		
265	6.61	13774	5951	3	3.70	B_1683GH180R4	

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
25 (CONT.)	203	8.64	15278	7779	3	3.70	B_1683GH180R4
	172	10.17	15278	9157	3	3.71	
	150	11.67	16566	10507	3	3.67	
	141	12.41	16566	11173	3	3.70	
	108	16.21	16566	14595	3	3.70	
	92	19.09	17607	17188	3	3.70	
	80	21.90	17607	19718	3	3.67	
	72	24.14	17607	21735	3	3.49	
	61	28.54	18949	25696	3	3.32	
	54	32.53	18949	29289	3	3.24	
	51	34.55	18949	31107	3	3.70	
	39	45.15	18949	40651	3	2.94	
	33	53.18	18949	47881	3	2.50	
	29	60.99	18949	54913	3	2.18	
	26	67.22	18949	60522	3	1.97	
22	79.49	18949	71569	3	1.67		
19	90.60	18949	81572	3	1.46		
17	104.18	18949	93799	3	1.27		
15	119.09	18949	107224	3	1.11		
30	246	7.10	6907	7671	3	3.09	B_1283GH180S4
	212	8.26	6907	8924	3	2.85	
	191	9.16	6907	9897	3	2.60	
	161	10.88	6907	11755	3	2.24	
	139	12.56	6907	13570	3	1.97	
	135	13.00	6907	14046	3	2.51	
	116	15.13	6907	16347	3	2.25	
	104	16.76	6907	18108	3	2.10	
	88	19.92	6907	21522	3	1.86	
	76	22.99	6907	24839	3	1.63	
	65	27.02	6907	29193	3	1.40	
	57	30.61	6907	33072	3	1.25	
	49	35.92	6907	38809	3	1.07	
	362	4.83	9207	5218	3	3.09	B_1483GH180S4
	272	6.43	9207	6947	3	3.09	
235	7.44	10246	8038	3	3.09		
199	8.79	10246	9497	3	3.06		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
30 (CONT.)	179	9.77	10246	10556	3	3.09	B_1483GH180S4
	135	13.00	11162	14046	3	3.09	
	116	15.05	11162	16260	3	3.09	
	98	17.77	11951	19199	3	3.06	
	88	19.84	11951	21436	3	2.91	
	75	23.19	11951	25055	3	2.70	
	66	26.58	11951	28718	3	2.38	
	57	30.74	12561	33212	3	2.08	
	56	31.10	12561	33601	3	2.11	
	42	41.38	12561	44708	3	1.58	
	37	47.91	13027	51763	3	1.37	
	31	56.57	13027	61120	3	1.16	
	28	63.16	13027	68240	3	1.04	
	265	6.61	13774	7142	3	3.09	
	203	8.64	15278	9335	3	3.09	
	172	10.17	15278	10988	3	3.09	
	150	11.67	16566	12609	3	3.06	
	141	12.41	16566	13408	3	3.09	
	108	16.21	16566	17514	3	3.09	
	92	19.09	17607	20625	3	3.09	
	80	21.90	17607	23661	3	3.06	
	72	24.14	17607	26082	3	2.91	
	61	28.54	18949	30835	3	2.77	
	54	32.53	18949	35146	3	2.70	
	51	34.55	18949	37329	3	3.09	
	39	45.15	18949	48781	3	2.45	
	33	53.18	18949	57457	3	2.08	
	29	60.99	18949	65895	3	1.81	
26	67.22	18949	72626	3	1.65		
22	79.49	18949	85883	3	1.39		
19	90.60	18949	97887	3	1.22		
17	104.18	18949	112559	3	1.06		
40	246	7.10	6907	10228	3	2.32	B_1283GH200T4
	212	8.26	6907	11899	3	2.14	
	191	9.16	6907	13196	3	1.95	
	161	10.88	6907	15673	3	1.68	

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
40 (CONT')	139	12.56	6907	18094	3	1.48	B_1283GH200T4
	135	13.00	6907	18727	3	1.88	
	116	15.13	6907	21796	3	1.69	
	104	16.76	6907	24144	3	1.57	
	88	19.92	6907	28696	3	1.39	
	76	22.99	6907	33119	3	1.22	
	65	27.02	6907	38924	3	1.05	
	362	4.83	9207	6958	3	2.32	B_1483GH200T4
	272	6.43	9207	9263	3	2.31	
	235	7.44	10246	10718	3	2.32	
	199	8.79	10246	12663	3	2.29	
	179	9.77	10246	14074	3	2.32	
	135	13.00	11162	18727	3	2.32	
	116	15.05	11162	21681	3	2.32	
	98	17.77	11951	25599	3	2.29	
	88	19.84	11951	28581	3	2.18	
	75	23.19	11951	33407	3	2.02	
	66	26.58	11951	38290	3	1.79	
	57	30.74	12561	44283	3	1.56	
	56	31.10	12561	44802	3	1.58	
	42	41.38	12561	59611	3	1.19	
	37	47.91	13027	69018	3	1.03	
	265	6.61	13774	9522	3	2.32	B_1683GH200T4
	203	8.64	15278	12447	3	2.31	
	172	10.17	15278	14651	3	2.32	
	150	11.67	16566	16811	3	2.29	
	141	12.41	16566	17877	3	2.31	
	108	16.21	16566	23352	3	2.32	
	92	19.09	17607	27501	3	2.32	
	80	21.90	17607	31549	3	2.29	
72	24.14	17607	34775	3	2.18		
61	28.54	18949	41114	3	2.08		
54	32.53	18949	46862	3	2.03		
51	34.55	18949	49772	3	2.32		
39	45.15	18949	65042	3	1.84		
33	53.18	18949	76610	3	1.56		

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
40 (CONT')	29	60.99	18949	87860	3	1.36	B_1683GH200T4
	26	67.22	18949	96835	3	1.23	
	22	79.49	18949	114511	3	1.04	
50	362	4.83	9207	8697	3	2.72	B_1483GH225U4
	272	6.43	9207	11579	3	2.53	
	235	7.44	10246	13397	3	2.33	
	199	8.79	10246	15828	3	2.11	
	179	9.77	10246	17593	3	2.72	
	135	13.00	11162	23409	3	2.53	
	116	15.05	11162	27101	3	2.33	
	98	17.77	11951	31999	3	2.07	
	88	19.84	11951	35726	3	1.87	
	75	23.19	11951	41759	3	1.62	
	66	26.58	11951	47863	3	1.43	
	57	30.74	12561	55354	3	1.25	
	56	31.10	12561	56002	3	1.26	
	265	6.61	13774	11903	3	2.34	B_683GH225U4
	203	8.64	15278	15558	3	2.26	
	172	10.17	15278	18313	3	2.21	
	150	11.67	16566	21014	3	2.12	
	141	12.41	16566	22347	3	2.33	
	108	16.21	16566	29190	3	2.26	
	92	19.09	17607	34376	3	2.21	
80	21.90	17607	39436	3	2.12		
72	24.14	17607	43469	3	2.00		
61	28.54	18949	51392	3	1.78		
54	32.53	18949	58577	3	1.62		
51	34.55	18949	62215	3	1.92		
39	45.15	18949	81302	3	1.47		
33	53.18	18949	95762	3	1.25		
29	60.99	18949	109826	3	1.09		
60	362	4.83	9207	10437	3	2.27	B_1483GH225V4
	272	6.43	9207	13894	3	2.11	
	235	7.44	10246	16077	3	1.94	
	199	8.79	10246	18994	3	1.76	
	179	9.77	10246	21112	3	2.27	

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------



SELECTION

RIGHT ANGLE HELICAL BEVEL INTEGRAL GEARMOTORS (RHB) - 1750 RPM 60 Hz

INPUT POWER (HP)	SPEED (RPM)	RATIO	OHL (LBF) (B)	OUTPUT TORQUE (LB-IN)	GEAR STAGE	SERVICE FACTOR (SF)	CATALOG NUMBER
60 (CONT')	135	13.00	11162	28091	3	2.11	B_1483GH225V4
	116	15.05	11162	32521	3	1.94	
	98	17.77	11951	38398	3	1.72	
	88	19.84	11951	42871	3	1.56	
	75	23.19	11951	50110	3	1.35	
	66	26.58	11951	57436	3	1.19	
	57	30.74	12561	66425	3	1.04	
	56	31.10	12561	67203	3	1.05	
	265	6.61	13774	14283	3	1.95	B_1683GH225V4
	203	8.64	15278	18670	3	1.88	
	172	10.17	15278	21976	3	1.84	
	150	11.67	16566	25217	3	1.77	
	141	12.41	16566	26816	3	1.95	
	108	16.21	16566	35027	3	1.88	
	92	19.09	17607	41251	3	1.84	
	80	21.90	17607	47323	3	1.77	
	72	24.14	17607	52163	3	1.67	
	61	28.54	18949	61671	3	1.49	
	54	32.53	18949	70293	3	1.35	
	51	34.55	18949	74658	3	1.60	
	39	45.15	18949	97563	3	1.22	
33	53.18	18949	114914	3	1.04		
75	265	6.61	13774	17854	3	1.61	B_1683GH250W4
	203	8.64	15278	23337	3	1.57	
	172	10.17	15278	27470	3	1.54	
	150	11.67	16566	31522	3	1.48	
	141	12.41	16566	33520	3	1.61	
	108	16.21	16566	43784	3	1.57	
	92	19.09	17607	51563	3	1.54	
	80	21.90	17607	59153	3	1.48	
	72	24.14	17607	65204	3	1.44	
	61	28.54	18949	77089	3	1.38	
	54	32.53	18949	87866	3	1.30	
	51	34.55	18949	93322	3	1.28	

(B) See Footnote page on inside back cover

MOUNTING POSITIONS PAGE RHB-7	SELECTION OIL QUANTITIES PAGE RHB-7	SELECTION REDUCER PAGE RHB-17	DIMENSIONS PAGE RHB-92
----------------------------------	--	----------------------------------	---------------------------